

ARE-A4

MULTIFUNCTIONAL CHARGER

- Compatible with different battery types
- Multiple protection
- LCD screen for charging display
- AC and DC charging supported



1 CHARGER FOR 9 BATTERY TYPES

Compatible with kinds of battery types, four batteries can be charged simultaneously

Li-ion batteries: 10440, 14500, 16340, 18650, 21700, 26650

Ni-MH / Ni-Cd: AA, AAA, C



LCD SCREEN FOR CHARGING DISPLAY

After connecting to the power supply, the LCD screen will display the inserted battery types and voltages, and battery level will be displayed through battery status bar.

 0-20%	 60%-80%
 20%-40%	 80%-99%
 40%-60%	 100%

THE FOUR CHANNELS ARE SEPARATELY CONTROLLED BY THE FOUR BUTTONS.

Single click the button, the screen will cycle through battery voltage(V)→charging current(mA)→charging time(Time).

Long press any button to turn off the LCD screen. Single click the button will turn on the LCD screen again.

Note: Battery levels will not be displayed without power supply connected.



SUPPORT AC AND DC CHARGING CONVENIENT CHARGING IN A CAR

Supports AC100-240V/50-60hz
and DC12-24V;

Charging can be fulfilled both at
home and in a car;

Keep a ready battery anytime.



Note: Car adapter sold separately



PRODUCT FEATURES

- ⦿ Input: AC100-240V/50-60Hz/0.6A (max) or DC12-24V / 2.0A (max)
- ⦿ Rated output power: 6W (Ni-MH/ Ni-Cd), 16.8W (Li-ion)
- ⦿ Output: 4.2V/1.0A : 10440, 14500, 16340, 18650, 21700, 26650Li-ion battery. 1.5V, 1.0A : AA, AAA, C Ni-MH / Ni-Cd battery
- ⦿ Size: 5.89" Length × 4.09" Width × 1.59" Height / 149.5 x 104 x 40.5 mm
- ⦿ Weight: 9.35 oz / 265g (excluding charging cable)
- ⦿ Operating temperature: -20°C to 50°C
- ⦿ Operating Humidity: 5% to 90%
- ⦿ Storage Temperature: -20°C to 80°C
- ⦿ UL, PSE, GS, FCC, CE, RoHS, WEEE, CB