



Tripod Ref. PN 800

- ▶ For access in confined spaces.
- ▶ With two mounted pulleys at the head of the Tripod in the prolongation of the main leg for passing a cable.
- ▶ Having two auxiliary eye bolts as attachment points.
- ▶ Aluminium alloy cast head, legs in Aluminium.
- ▶ Steel support-shoes provided with rubber sole to increase friction and impart more stability.
- ▶ Strength of anchorage point greater than 12 kN.
- ▶ **Every Tripod is provided with inbuilt fixture for attaching our winch PN 801, PN 817, PN 818, PN 818 SR, PN 801(40) (can be supplied without this fixture on special request).**
- ▶ PN 800 (7ft) can also be used with Retrieval Fall Arrester Blocks PCGS 10R, PCGS 20R & PCGS 30R with the help of their specialized mounting brackets respectively.
- ▶ Every Tripod is provided with Tripod Bag Ref. PN 904(7ft)(BL)

LENGTH	SPECIFICATION	COMPLIANCE
7 ft.	<ul style="list-style-type: none"> ▶ Fully adjustable telescopic legs, adjustable height from 1.15m to 2.15m ▶ Wheelbase (Footprint) : 1.5m Diameter ▶ Weight : 12.15 kgs ▶ Maximum Load Capacity : 500kg 	EN 795:2012 TYPE B
10 ft.	<ul style="list-style-type: none"> ▶ Fully adjustable telescopic legs, adjustable height from 1.9m to 3.07m ▶ Wheelbase (Footprint) : 1.7m Diameter ▶ Weight : 16.8 kgs ▶ Maximum Load Capacity : 500kg 	

Ref. No.	PN 801(20)	PN 801(25)
Length	20m	25m
Weight	7.54kg	7.94kg



**Tripod Bag
Ref. PN 904(7ft)(BL)**



**Winch
Ref. PN 801**

The KARAM Winch is used for raising or lowering personnel or material.

- ▶ To be used for raising or lowering of personnel or material into confined spaces
- ▶ Equipped with bolting fixture for robust fitting on to the tripod PN 800
- ▶ Maximum lifting load capacity as per EN 1496 : 135 kgs
- ▶ Maximum lifting load capacity as per machinery directive 2006/42/EC : 250 kgs
- ▶ Length: 20m & 25m
- ▶ Conforms to EN 1496:2006 (Class A)
- ▶ To be used with a Retractable Fall Arrester when deployed for raising or lowering a person
- ▶ Can also be fitted to KARAM K-Pod PN 900
- ▶ Also available with the SS Wire Rope instead of GI. Respective references with SS Wire Rope shall be PN 801(20)SS & PN 801 (25)SS.

Mounting Brackets for Tripod Ref. PN 800(7ft) & PN 800(10ft)

Mounting Bracket	Picture	Bracket used for Mounting
Ref. PN 800 A (R)(09)		For 30M Retrieval Block Ref. PCGS 30R
Ref. PN 800 A (R)(10)		For 20M Retrieval Block Ref. PCGS 20R
Ref. PN 800 A (R)(11)		For 10M Retrieval Block Ref. PCGS 10R