



PYRAMEX
Perform At Your Peak™

Venture 3® ANSI CE CSA AUS BALLISTIC



VENTILATED
FRAME



ADJUSTABLE
NOSEPIECE



CO-INJECTED
TEMPLES

Soft, adjustable ventilated nosepiece

Ventilated frame

Soft, adjustable co-injected rubber temples

Passes MIL-PRF 32432 High Velocity
Impact Standards

Part No.	Black Frame
SB57100 ●●●●	Clear
PYSB 57100* ●●●●	Clear
SB57100T ●●●●	AF Clear H2X
SB57200 ●●●●	Gray
SB57200T ●●●●	AF Gray H2X
SB57300 ●●●●	Amber
PYSB 57300* ●●●●	Amber
SB5750SFT ●●●●	AF 5.0 IR Filter H2X
SB57600 ●●●●	Infinity Blue
SB5760SFT ●●●●	AF 3.0 IR Filter H2X
SB57700 ●●●●	Silver Mirror
SB57800 ●●●●	I/O Mirror

*Pyramex retail packaged product



Venture 3®

General Specifications

Weight: 28 gm
 PD: 68 mm
 Bridge: 12.8 mm
 Lens base: 9.5 curve
 Lens size diagonal: 82 mm
 Lens size vertical: 46.6 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 150 - 163 mm
 Overall width (hinge - hinge): 139.4 mm
 Closest point between temple tips: 91 mm
 Closest point between lens: 13.1 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temple tips: polycarbonate and thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Sleeve: polycarbonate
 Nosepiece: bridge - polycarbonate and nose pad - polyvinyl chloride (PVC)
 Side shields: polycarbonate

Part No.	Lens Marking	Frame Marking
SB 57100	P + U6	P Z87 +/P c SEI CAN/CSA Z94.3-15
SB 57100T	P + U6	P Z87 +/P c SEI CAN/CSA Z94.3-15
SB 57200	P + U6 L2.5	P Z87 +/P c SEI CAN/CSA Z94.3-15
SB 57200T	P + U6 L2.5	P Z87 +/P c SEI CAN/CSA Z94.3-15
SB 57300	P + U6	P Z87 +/P c SEI CAN/CSA Z94.3-15
SB 5750SFT	P + W5	P Z87 +
SB 57600	P + S	P Z87 +/P c SEI CAN/CSA Z94.3-15
SB 5760SFT	P + W3	P Z87 +
SB 57700	P + S	P Z87 +/P c SEI CAN/CSA Z94.3-15
SB 57800	P + U6 L1.7	P Z87 +/P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special purpose
 W: Welding filter
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

